

Përdorimi - fasada ventiluese



KNAUF INSULATION TP 435 B



Trashësia (mm)	Gjatësia (mm)	Gjërësia (mm)	Rolne në pako	m ² /pako	Pako/paletë	m ² /paletë	Çmimi €/m ² (pa TVSH)
40	1250	600	12	9.0	20	180.00	
50	1250	600	10	7.5	20	150.00	
60	1250	600	8	6.0	20	120.00	
80	1250	600	6	4.5	20	90.00	
100	1250	600	5	3.8	20	75.00	
120	1250	600	4	3.0	20	60.00	
140	1250	600	3	2.3	20	45.00	

Namenjena je za toplotnu, zvučnu zaštitu i zaštitu od požara:

- ventilisanih fasada
- Proizvod je jednostrano kaširan na crnom staklenom voalu.



Certifikata EC mbi konformitetin
0764.CPD.0145



Përçueshmëria e deklaruar termike
 $\lambda_D = 0.034 \text{ W/mK}$



Klasa e reagimit ndaj zjarrit
A1



Thihja e ujit
Afatshkurtër: $W_p < 1 \text{ kg/m}^2$
Afatgjatë: $W_p < 3 \text{ kg/m}^2$

with **ECOSE**
TECHNOLOGY